

# tesapack<sup>®</sup> eco & strong



BNR 58153, 58154, 58155, 58156, 58226, 58227

## Product Features

- Strong PP backing made from 100% recycled plastic
- Core made from 100% recycled cardboard
- Label made from paper
- Solvent-free adhesive with high UV-resistance
- High sealing security
- Even, low noise unwinding
- Suitable for use with all available tesapack<sup>®</sup> hand dispensers
- The recycled content has been approved by the independent certification organisation DIN CERTCO belonging to the TÜV Rheinland (German technical control board).

## Product Description

tesapack<sup>®</sup> eco & strong is a more eco-friendly packaging tape made from 100% recycled plastic. It is free from PVC and solvents

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |       |                    |                     |
|--------------------|-------|--------------------|---------------------|
| • Backing material | BOPP  | • Type of adhesive | water-based acrylic |
| Recycled           | 100 % | • Total thickness  | 57 µm               |

## Properties/Performance Values

- |                          |               |                     |           |
|--------------------------|---------------|---------------------|-----------|
| • Adhesive strength      | High adhesion | • Solvent free      | yes       |
| • Ageing resistance (UV) | yes           | • Suitable surfaces | Cardboard |
| • Applicationfield       | Home, Office  | • Tear resistance   | yes       |
| • Elongation at break    | 80 %          | • Tensile strength  | 40 N/cm   |
| • Hand tearability       | no            | • Unwind force n/cm | 3.7 N/cm  |
| • Low noise unwinding    | yes           |                     |           |

## Certificates

Certified according to  
Din Certco

# tesapack<sup>®</sup> eco & strong

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=58153>